Voyager Star

96627657 <VOYAGER STAR PRIM ESC E3 SET L750

Voyager Star

High performance, Primata module with LED emergency lighting luminaire, Self contained luminaire, manual test (3 hours) and escape route optic.. Profiled sheet steel, coated with polyester paint. Lens:. IP20,. Tool-free connection to Primata continuous row lighting system. Electrical connection (230VAC) via maximum 2.5mm² cable, loop in - loop out possible. Optimum thermal management via heat sink. Maintained mode: +5°C to +30°C, non-maintained mode: +5°C to +35°C; power supply:220-240 V AC (+/- 10%), 50-60 Hz Complete with LEDs..

Luminaire input power: 4 W
Weight: 2 kg

TLG_VSTR_F_PRIM_ExD_ESC_WH.jpg

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Voyager Star

96627657 <VOYAGER STAR PRIM ESC E3 SET L750

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting