Discontinued

96207116 OPTUS IV D 2x49W HF WHI DSB

Discontinued

A surface mounted and suspended luminaire with a modern slim design, suitable for both office and school applications. For 2x49W Light Source: 2 x T16 / 49W lamp(s). electronic - fixed output. Body: extruded aluminium with powder coated aluminium, matt white finish. End Caps: die-cast zinc, and satinbrite louvre in anodised aluminium. Class I electrical, IP20. Electrical connection via factory fitted 3 x 2 x 2.5 mm² piano key terminal block and cable clamp. Key hole fixing centres 1300mm. Lamps to be ordered separately.

Dimensions: 1509 x 165 x 61 mm
Luminaire input power: 110.6 W
Weight: 3 kg

TLG_OPT4_F_2SURWHISB.jpg



TLG_OPT4_M_SLD1a.wmf

All values marked with an * are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Discontinued

96207116 OPTUS IV D 2x49W HF WHI DSB

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting