

# Chalice 3

93900898 CHAL3 100 1400-830 EHF E3 RSB

THORN

## Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø100mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54\_IP20. Complete with 3000K LED

Dimensions: Ø119 x 75 mm  
Luminaire input power: 16.7 W  
Luminaire luminous flux: 1470 lm  
Luminaire efficacy: 88 lm/W  
Weight: 0.86 kg



TLG\_CHAL3\_F\_100\_RSB\_EM.jpg



TLG\_CHAL3\_M\_EHF100L.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## Chalice 3

93900898 CHAL3 100 1400-830 EHF E3 RSB

THORN