

# Chalice 3

93901200 CHAL3 150 3000-840 EHF E3 RMB

## Chalice 3


A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical, IP54\_IP20. Complete with 4000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø174 x 94 mm  
Luminaire input power: 30.1 W  
Luminaire luminous flux: 3343 lm  
Luminaire efficacy: 111 lm/W  
Weight: 1.13 kg



TLG\_CHAL3\_F\_150\_RMB\_IP54\_EMG.jpg



TLG\_CHAL3\_M\_EHF150.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

## Chalice 3

93901200 CHAL3 150 3000-840 EHF E3 RMB

THORN