

## R2L2

96266624 R2L2 M 84L50 740 WR CL2 GY

### R2L2

A medium size LED road lighting lantern with 84 LEDs driven at 500mA with Wide Road optic. LED driver Programmable. Class II electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm  
 Luminaire input power: 123 W  
 Luminaire luminous flux: 19514 lm  
 Luminaire efficacy: 159 lm/W  
 Weight: 13.1 kg  
 Scx: 0.06 m<sup>2</sup>



TLG\_R2L2\_F\_MPDB.jpg



TLG\_R2L2\_M\_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

**R2L2**

**96266624 R2L2 M 84L50 740 WR CL2 GY**

**THORN**