

ArrowFlex 2C

22665279 ARROWFLEX 2C LED800-827 IP44

THORN

ArrowFlex 2C

5m length of compact and flexible LED strip for indirect and emotional lighting, cove lighting and backlighting for horizontal or vertical niches. Can be cut on site on pre-defined cutting marks. Self adhesive tape on the reverse, for surface mounting to straight, clean surfaces. 120 LED/m for high lighting homogeneity.


Complete with 2700K LED, 9.6W/m, 800 lm/m, 120° beam angle, IP44

Dimensions: 5000 x 10 x 4 mm
Luminaire input power: 9.4 W
Luminaire luminous flux: 864 lm
Luminaire efficacy: 92 lm/W
Weight: 0.6 kg

Rated median useful life: 50000h



TLG_ARFC_F_PDB.jpg



TL_ARFC_M_800.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting