

Piazza II LED

96632757 PIAZZA II LED 1690-830 HF ANT

THORN

Piazza II LED

A robust Wall mounted luminaire. Electronic, fixed output control gear. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 3000K LED.

Dimensions: 381 x 196 x 305 mm

Luminaire input power: 15.1 W


Luminaire luminous flux: 1815 lm

Luminaire efficacy: 120 lm/W

Weight: 2.8 kg



TLG_PIA2_F_PDB.jpg



TLG_PIA2_M_LD1.wmf

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Piazza II LED

96632757 PIAZZA II LED 1690-830 HF ANT

THORN