

# Aerie

THORN

96632912 ARW 24L70-740 WSC CL CL1 W5 T76 ANT

## Aerie

A discreet, post top LED lantern with a timeless design. LED driver for 24 LEDs, driven at 700mA with Wide Street Comfort (asymmetrical) distribution. Class I electrical, IP66, IK10. Canopy and base: corrosion resistant die-cast powder coated aluminium suitable for C5 environments, finished textured anthracite (close to RAL7043). Enclosure: wide UV stabilised polycarbonate with clear finish. Complete with 4000K LED. Post top mounting to  $\text{\O}76\text{mm}$  column. Pre-wired with 5m cable.

Dimensions:  $\text{\O}602 \times 586 \text{ mm}$   
Luminaire input power: 51 W  
Luminaire luminous flux: 7796 lm  
Luminaire efficacy: 153 lm/W  
Weight: 11.12 kg  
Scx:  $0.172 \text{ m}^2$



TLG\_AERI\_F\_W\_CL.jpg



TLG\_AERI\_M\_T76\_W.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of  $25^{\circ}\text{C}$ .

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Aerie**

**96632912 ARW 24L70-740 WSC CL CL1 W5 T76 ANT**

**THORN**