

Durolight

96633067 DUROLIGHT-S 4000-830 HFIX L1350

THORN

Durolight

Anti-vandal Surface mounted LED luminaire. Electronic, DALI dimmable control gear. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam. Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 3000K LED

Dimensions: 1350 x 290 x 66 mm

Luminaire input power: 37.6 W


Luminaire luminous flux: 3965 lm

Luminaire efficacy: 105 lm/W

Weight: 15 kg



TLG_DURO_F_MCE.jpg



TLG_DURO_M_LDS.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting