

## Punch

**96635407 PUNCH 3 LRO MSP 6600-840 L15 HFIX E3D**

### Punch

A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic, with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 4000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1542 x 162 x 50 mm  
 Luminaire input power: 54.1 W  
 Luminaire luminous flux: 6939 lm  
 Luminaire efficacy: 128 lm/W  
 Weight: 6.2 kg



TLG\_PNCH\_F\_LRO\_suspended\_on\_PDB.jpg



TLG\_PNC3\_M\_PLEXD.wmf

This product contains light sources of energy efficiency class D.

# Punch

96635407 PUNCH 3 LRO MSP 6600-840 L15 HFIX E3D

THORN