



Thor Bollard

Elegant vandal resistant bollard with high performance optic offering a comfortable light and energy saving solutions

- Best in class LED optic provides a comfortable, low glare direct and indirect light with asymmetric or symmetric distribution, sympathetic to users with a lower viewing angle
- Durable and vandal resistant (IK10 40 joules for the slim version)
- Bi power dimming and presence detection options reduce energy consumption
- Available in two sizes – slim and wide – with the wide version also suitable for use as street furniture



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.



96264246

Material/Finish

Column and base: aluminium

Canopy: die-cast aluminum (EN AC 44300, standard corrosion class C5).

Diffuser: clear anti UV Polycarbonate

Reflector: white Polycarbonate

Gear Box: Polypropylene

Canopy and Column colour: powder coated dark grey (close to 7043)

Installation/Mounting

Slim version: suitable for Root and Flange mounting: 4 x anchor bolts M14 (96009822 to be ordered separately), spacing: 150mm.

Wide version: suitable for Flange mounting: 4 x anchor bolts M14 (to be ordered separately), spacing: 200mm.

Ready to install: prewired fittings to be connected with a connection box (to be ordered separately) through the anti vandal access door (via Torx hollow T30)

For RGB and Bi power versions choose the colour of the decorative led band or deactivate the Bi Power function at installation through the access door.

Gear box (including the driver) and head (including the LEDs) are easily replaceable as spares.

Thor Bollard

Ordering Guide Supplied complete with LEDs.

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
MGR base adaptors				
MGR SPIKE RAZE/DCO/THOR/CANDLE BOL			10	96635553
MGR BASE RAZE/DCO/THOR/CANDLE BOL			6	96635554