

Altis Sport (APAC)

A versatile area floodlighting LED luminaire suited for wide ranging weather climate in APAC with best in class lifetime

- Unique quality of light with flickerfree operation suitable for HDTV broadcasting and Super Slow Motion Images
- Flexible optical system optimising lighting distributions for best in class results
- Compact and low weight for minimal structural costs
- Fully controllable solution enabling instant lighting, stepped illumination levels and event lighting with dynamic lighting scenarios



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.

Material/Finish

Body: die-cast aluminium, painted dark sandy grey (RAL 7043)

Frame and stirrup: die-cast aluminium, painted dark sandy grey (close to RAL 7043)

Glass: 5mm toughened, meeting requirements of IEC 60598-2-5 Screws: stainless steel

Installation/Mounting

Stirrup fixed by a single bolt through Ø22mm hole or 105x17mm oblong hole, or by twin bolts through Ø15mm hole. Reversible stirrup allows hang down position. Frame fixed to stirrup with M10 Hexagonal screw and M8 set screw. Tilttable LED modules fixed on frame with M8 screws and M5 set screw.

The LED modules are pre-wired with a 1m long cable and connected to a single harness. Electrical connection to the floodlight is done via a single multi-core cable (female connector supplied for quick plug-in connection); gear tray IP21 or gear box IP65 are installed remotely and supplied separately.

Precision aiming device available and adjustable on top or bottom of LED module.

Ordering Guide

| Description | ILCOS Code | Socket | Wt (kg) | SAP Code |
|-------------------------------------|------------|--------|---------|----------|
| Altis Sport, Narrow beam | | | | |
| ALTIS S 396L NB CL1 L957 | LED | | 30,5 | 22663269 |
| ALTIS S 396L NB CL1 L840 | LED | | 30,5 | 22663272 |
| ALTIS S 396L NB CL1 L740 | LED | | 30,5 | 22664560 |
| Altis Sport, Medium beam | | | | |
| ALTIS S 396L MB CL1 L957 | LED | | 30,5 | 22663271 |
| ALTIS S 396L MB CL1 L840 | LED | | 30,5 | 22663273 |
| ALTIS S 264L MB CL1 L957 | LED | | 23,1 | 22663278 |
| ALTIS S 264L MB CL1 L840 | LED | | 23,1 | 22663281 |
| ALTIS S 396L MB CL1 L740 | LED | | 30,5 | 22664552 |
| Altis Sport, Wide beam | | | | |
| ALTIS S 396L WB CL1 L957 | LED | | 30,5 | 22663280 |
| ALTIS S 396L WB CL1 L840 | LED | | 30,5 | 22663274 |
| ALTIS S 264L WB CL1 L957 | LED | | 23,1 | 22663279 |
| ALTIS S 264L WB CL1 L840 | LED | | 23,1 | 22663290 |
| ALTIS S 396L WB CL1 L740 | LED | | 30,5 | 22664553 |
| Altis Sport, Asymmetric beam | | | | |

Altis Sport (APAC)

| Description | ILCOS Code | Socket | Wt (kg) | SAP Code |
|--------------------------|------------|--------|---------|----------|
| ALTIS S 396L A4 CL1 L840 | LED | | 30,5 | 22663275 |
| ALTIS S 396L A5 CL1 L840 | LED | | 30,5 | 22663276 |
| ALTIS S 396L A6 CL1 L840 | LED | | 30,5 | 22663277 |
| ALTIS S 264L A4 CL1 L840 | LED | | 23,1 | 22663308 |
| ALTIS S 264L A5 CL1 L840 | LED | | 23,1 | 22663309 |
| ALTIS S 264L A6 CL1 L840 | LED | | 23,1 | 22663322 |
| ALTIS S 396L A4 CL1 L740 | LED | | 30,5 | 22664554 |
| ALTIS S 396L A5 CL1 L740 | LED | | 30,5 | 22664555 |
| ALTIS S 396L A6 CL1 L740 | LED | | 30,5 | 22664556 |

| Altis Sport, Control gear | | | | |
|---------------------------|--|--|----|----------|
| GB ALTIS IP66 396L105 CL1 | | | 14 | 22663323 |
| GB ALTIS IP66 396L70 CL1 | | | 14 | 22663324 |
| GB ALTIS IP66 264L105 CL1 | | | 13 | 22663325 |
| GB ALTIS IP66 264L70 CL1 | | | 13 | 22663326 |