

ArrowFlex 2C


Compact LED flexible strip offering shadow free lighting for adding atmosphere in retail and interior application

- Output lumen 400-800lm/m with lumen efficacy more than 80lm/W
- Available in a range of cool to warm whites 2700K, 3000K, 4000K to suit a great variety of applications
- IP44 ingress protection standard
- Professional heatsink design to guarantee 50khrs lighting performance



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.





Material/Finish

Body: Flexible PCB Diffuser: PVC tube

Installation/Mounting

Surfaced mounted: Attached to any smooth and clean surface via self-adhesive tape on the back side of the flexible strip and then apply mounting clip to secure the flexible strip firmly

Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
ArrowFlex 2C				
ARROWFLEX 2C LED400-827 IP44	LED		0,6	22665276
ARROWFLEX 2C LED400-830 IP44	LED		0,6	22665277
ARROWFLEX 2C LED400-840 IP44	LED		0,6	22665278
ARROWFLEX 2C LED800-827 IP44	LED		0,6	22665279
ARROWFLEX 2C LED800-830 IP44	LED		0,6	22665280
ARROWFLEX 2C LED800-840 IP44	LED		0,6	22665281